

Patriot

Remtron® Control Systems



HIGH-VALUE, RELIABLE CRANE CONTROLS

HIGHLIGHTS

- compact and extremely tough keypad operator control
- A rugged and reliable system means less downtime
- Superior factory support with an unconditional one-year warranty
- Made entirely in the USA

FEATURES

- Up to 15 Functions
- On/Alarm and Off/Stop Buttons
- Up to 3 Two-Step Discrete Rockers
- Up to 6 Push Buttons
- Optional Multiplex Selector
- LED for Operational Status
- Long-life disposable batteries

APPLICATIONS

The systems are built to survive in aggressive industrial environments.

- Overhead Cranes
- Heavy Machinery
- Ship Loaders
- Metal Fabrication
- Amusement Parks
- Lifting Equipment

COMPLIANCE

UL508 Electrical Safety

SYSTEM MATRIX

Control Scheme	OCU	MCU
3 Motion/1 Speed +Horn +Stop	25T08A	25R11A-S08A
2 Motion/2 Speed +Horn +Stop	25T10A	25R11A-10A
3 Motion/2 Speed +Horn +Stop	25T11A	25R11A 3- and 4-Wire Hoist Config
3 Motion/2 Speed w/A/B/Both Option +Horn +Stop and 1 Aux	25T15A	25R15A 3- and 4-Wire Hoist Config

TECHNICAL DATA AND SPECIFICATIONS

ELECTRONIC DATA	
Commands	See matrix on front
Digital circuitry	Microprocessor technology
System addresses	16-bit, 65,535 unique addresses
Energy-saving mode	Automatic shutdown (15 minutes)
Supply voltage	2- AA batteries
Autonomy	>130 hours typical

OPERATION AND INDICATION	
Actuators	Up to 3 dual step rocker switches, horn, stop, Aux and A/B/both
LED	1 status LED for active, low battery

RF	
Frequency range	902-927 MHz 85 RF channels
Transmitter output power	1mW license exempt
Modulation	Packet Mode, FM
RF channel spacing	300 KHz
Antenna	Internal
FCC ID	T10A style EGT810TX (25T10A) T18A style ECT818TX (25T11A, 25T15A)

USA: +1.234.806.0018
Systems-US-Sales@lairdtech.com

Europe: +49.2151.4795.0
Systems-EU-Sales@lairdtech.com

Asia: +86.21.3120.0188
Systems-CN-Sales@lairdtech.com

Latin America: +55.19.3518.7030
Systems-BR-Sales@lairdtech.com

www.lairdcontrols.com/controls

PATRIOT_DS_EN_201811

Any information furnished by Laird Limited, its subsidiary companies and its agents (hereafter, "Laird") is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird disclaims liability for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect at the time of sale. A current copy of the Laird Terms and Conditions will be furnished upon request. This document is © Copyright 2018, Laird, all rights reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trademarks of Laird. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.

MECHANICAL DATA		
	OCU	MCU
Weight	T10A 0.25 kg (9 oz)	---
	T11A/T15A 0.28 kg (10 oz)	
Dimensions L x W x H	T10A 7 x 16.5 x 2.5 cm (2.8 x 6.5 x 1 in)	25.4x12.7x6.4 cm (10 x 5 x 2.5)
	T15A 7 x 20.5 x 2.5 cm (2.8 x 8.1 x 1 in)	
Housing	High-impact, fiber-reinforced nylon	Aluminum
	IP67, suitable for outdoor use	IP52, suitable for indoor use
Operating temperature	-29° to +71° C (-20° to +160° F)	
Vibration and shock	Vibration/impact and drop tested to 1m on concrete	
ACCESSORIES		
Batteries	2- standard AA	