

# Transport CS™

for Industrial Rail Operations

## FIXED MOUNT, COMPACT REMOTE CONTROL SYSTEM

---

### HIGHLIGHTS

- Compact, single-cabinet design reduces space requirement
  - Easy installation reduces maintenance and downtime
  - Designed to allow fast troubleshooting
  - Fewer maintenance and repair components for lower cost of ownership
  - Minimal training required for operation
- 

### FEATURES

- Compatible with Paddle or Toggle OCU
  - Horn & Bell control
  - Electric throttle control and monitoring
  - Electric reverser control and monitoring
  - Proportional Independent and Train Brake control
  - Emergency brake control
  - Digital display feedback
  - Heated LCU cabinet
  - Up to eight Talkback indicators
- 

### OPTIONAL FEATURES

- LED Talkback
  - Maintenance Terminal Options
  - Pitch& Catch
  - Vigilance and PTO
- 

### APPLICATIONS

Transport CS™ is designed exclusively for industrial rail operations in the US and Canada markets.

- Steel Mills
  - Grain Processing
  - Load-Out Facilities
  - Potash
  - Coal
  - Gravel
-

**TECHNICAL DATA AND SPECIFICATIONS**

CATEGORY	SPECIFICATIONS
<b>Dimensions (WxDxH)</b>	24" x 10" x 36" pneumatic connectors extend beyond these dimensions
<b>Enclosure</b>	Receiver, decoder and power supply are each contained in their own EMI-shielded compartment. System is enclosed in a single NEMA 4 enclosure, with user interface buttons and display accessible from outside the enclosure.
<b>Control voltage range</b>	32 VDC or 64 VDC fused @ 5 amps Special voltages available upon request
<b>Input voltage</b>	32 VDC or 64 VDC Special voltages available upon request
<b>Receiver frequency</b>	450-470 MHz
<b>Archive memory size</b>	32 MB



USA: +1.234.806.0018  
Systems-US-Sales@lairdtech.com

Europe: +49.2151.4795.0  
Systems-EU-Sales@lairdtech.com

Asia: +86.21.3120.0188  
Systems-CN-Sales@lairdtech.com

Latin America: +55.19.3518.7030  
Systems-BR-Sales@lairdtech.com

**[www.lairdcontrols.com/controls](http://www.lairdcontrols.com/controls)**

TRANSPORT CS<sup>™</sup>\_DS\_EN\_201811

*Any information furnished by Laird Limited, its subsidiary companies and its agents (hereafter, "Laird") is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird disclaims liability for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect at the time of sale. A current copy of the Laird Terms and Conditions will be furnished upon request. This document is © Copyright 2018, Laird, all rights reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trademarks of Laird. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.*